



WATER TYPE (GAS CARTRIDGE)

Fire Safe BRAND WATER TYPE FIRE EXTINGUISHERS ARE MANUFACTURED AS PER IS: 940 USEFUL FOR CLASS "A" AND FIRE INVOLVING MATERIAL LIKE WOOD, PAPER, IDEAL FOR OFFICES, SCHOOL, THEATERS, HOSPITALS, DEPARTMENTAL STORES, STORE ROOMS, APARTMENTS, HOTELS AND FURNITURE. EXTINGUISH FIRE BY BLANKETING DILUTION OF OXYGEN AND COOLING EFFECTS.

CAPACITY : 9 LTRS.
OPERATION : UPRIGHT
SPECIFICATION IS: 940
JET LENGTH 6 TO 10 MTRS.
DISCHARGE TIME: 60 TO 120 SEC.
% OF DISCHARGE: 95 TO 98%



DRY POWDER (CARTRIDGE TYPE)

Fire Safe BRAND DRY POWDER CARTRIDGE TYPE FIRE EXTINGUISHERS ARE MANUFACTURED AS PER IS: 2171 USEFUL FOR CLASS "B" & "C" AND FIRES INVOLVING MATERIAL LIKE OIL, FATS SOLVENTS, GASES, PAINT VARNISH, ELECTRICAL WIRING AND LIVE MACHINERY AND EXTINGUISHES FIRE BY BEATING DISPLACEMENT OF AIR AND DECOMPOSITION OF DRY POWDER EFFECTS.

CAPACITY : 1 TO 10 KGS.
OPERATION : UPRIGHT
SPECIFICATION IS: 2171
JET LENGTH 2 TO 8 MTRS.
DISCHARGE TIME: 8 TO 30 SEC.
% OF DISCHARGE: 85 TO 95%



CARBON DI-OXIDE

Fire Safe BRAND CARBON DI - OXIDE FIRE EXTINGUISHERS ARE MANUFACTURED AS PER IS: 2878 USEFUL FOR CLASS B & C FIRES INVOLVING MATERIAL LIKE INFLAMMABLE LIQUIDS, GASEOUS AND ELECTRICAL FIRE, OIL SPILLAGES, ETC. IDEAL FOR LIVE DELICATE MACHINERIES, FLAMMABLE LIQUIDS & GASES AND EXTINGUISHES FIRE BY BLANKETING DILUTION OF OXYGEN AND COOLING EFFECTS INVOLVING HIGH VOLTAGE ELECTRICAL EQUIPMENTS.

CAPACITY : 2 TO 22.5 KGS.
OPERATION : UPRIGHT
SPECIFICATION IS: 2878
DISCHARGE TIME: 8 TO 90 SEC.
% OF DISCHARGE: 95 TO 98%



MECHANICAL FOAM

Fire Safe BRAND MECHANICAL FOAM FIRE EXTINGUISHERS ARE MANUFACTURED AS PER IS: 10204 USEFUL FOR CLASS "A" & "B" AND FIRES INVOLVING MATERIAL LIKE OIL, PETROLEUM PRODUCTS, SOLVENTS, GREASE, PAINT AND EXTINGUISHES FIRE BY BLANKETING AND COOLING DOWN THE CONTAINER THE CONTENTS.

CAPACITY : 9 LTRS.
OPERATION : UPRIGHT
SPECIFICATION IS: 10204
JET LENGTH 6 TO 8 MTRS.
DISCHARGE TIME: 25 TO 90 SEC.
% OF DISCHARGE: 90 TO 95%



MMD (DGS) APPROVED EXTINGUISHERS

WATER TYPE 9 LTRS.
MECHANICAL FOAM 9 TO 50 LTRS.
DRY POWDER (CARTRIDGE) TYPE 5 TO 50 KGS.
CARBON DIOXIDE TYPE 2 KGS. TO 6.5 KGS.



CO₂ GAS CARTRIDGES

60 GMS. TO 300 GMS.

