

## WATER TYPE ( GAS CARTRIDGE ) TROLLEY MOUNTED



**Fire Fite BRAND WATER TYPE TROLLEY MOUNTED FIRE EXTINGUISHERS** ARE MANUFACTURED AS PER IS: 13085 REFILL AS PER IS: 4947 USEFUL FOR CLASS "A" AND FIRE INVOLVING MATERIAL LIKE WOOD, PAPER, IDEAL FOR OFFICES, SCHOOLS, THEATRES, HOSPITALS, DEPARTMENTAL STORES, STORE ROOMS, APARTMENTS, HOTELS AND FURNITURE. EXTINGUISH FIRE BY BLANKETING DILUTION OF OXYGEN AND COOLING EFFECTS.

CAPACITY : 50LTRS.  
OPERATION : UPRIGHT  
SPECIFICATION : IS:13085  
JET LENGTH : 10 TO 15 MTRS.  
DISCHARGE TIME : 60 TO 180SEC.  
% OF DISCHARGE : 95 TO 98%

## MECHANICAL FOAM TROLLEY MOUNTED



**Fire Fite BRAND MECHANICAL FOAM TROLLEY MOUNTED FIRE EXTINGUISHERS** ARE MANUFACTURED AS PER IS: 13086 USEFUL FOR CLASS "B" AND FIRES INVOLVING MATERIAL LIKE CHEMICALS, OILS, PETROLEUM PRODUCTS, SOLVENTS, GREASE, IDEAL FOR PAINT SHOP, OIL FIRED BOILER ROOMS, FLAMMABLE LIQUID STORAGE CELL AND YARD ETC. AND EXTINGUISHES FIRE BY BLANKETING AND COOLING DOWN THE CONTAINER THE CONTENTS.

CAPACITY : 50LTRS.  
OPERATION : UPRIGHT  
SPECIFICATION : IS:13086  
JET LENGTH : 10 TO 12 MTRS.  
DISCHARGE TIME : 90 TO 180SEC.  
% OF DISCHARGE : 90 TO 95%

## DRY POWDER TROLLEY MOUNTED



**Fire Fite BRAND DRY POWDER TROLLEY MOUNTED FIRE EXTINGUISHERS** ARE MANUFACTURED AS PER IS: 10658 USEFUL FOR CLASS "B" & "C" AND FIRES INVOLVING MATERIAL LIKE OIL, FATS SOLVENTS, GASES, PAINT VARNISH, ELECTRICAL WIRING AND LIVE MACHINERY AND EXTINGUISHES FIRE BY SEATING DISPLACEMENT OF AIR & DECOMPOSITION OF DRY POWDER EFFECTS.

CAPACITY : 25 TO 75 KGS.  
OPERATION : UPRIGHT  
SPECIFICATION : IS:10658  
JET LENGTH : 6 TO 15 MTRS.  
DISCHARGE TIME : 25 TO 60 SEC.  
% OF DISCHARGE : 85 TO 88%

## DRY POWDER (STORED PRESSURE)



**Fire Fite BRAND DRY POWDER STORE PRESSURE FIRE EXTINGUISHERS** ARE MANUFACTURED AS PER IS: 13049 USEFUL FOR CLASS "A" "B" & "C" FIRES INVOLVING MATERIAL LIKE OIL, FATS SOLVENTS, GASES, PAINT VARNISH, ELECTRICAL WIRING AND LIVE MACHINERY AND EXTINGUISHES FIRE BY SEATING DISPLACEMENT OF AIR AND DECOMPOSITION OF DRY POWDER EFFECTS.

CAPACITY : 0.5 TO 10 KGS.  
OPERATION : UPRIGHT  
SPECIFICATION : IS:13049  
JET LENGTH : 1.5 TO 8 MTRS.  
DISCHARGE TIME : 5 TO 25 SEC.  
% OF DISCHARGE : 85 TO 88%

## WATER TYPE (STORED PRESSURE)



**Fire Fite BRAND WATER TYPE STORED PRESSURE EXTINGUISHERS** ARE MANUFACTURED AS PER IS: USEFUL FOR CLASS "A" AND FIRE INVOLVING MATERIAL LIKE WOOD, PAPER, IDEAL FOR OFFICES, SCHOOLS, THEATRES, HOSPITALS, DEPARTMENTAL STORES, STORE ROOMS, APARTMENTS, HOTELS AND FURNITURE. EXTINGUISH FIRE BY BLANKETING DILUTION OF OXYGEN AND COOLING EFFECTS.

CAPACITY : 09 LTRS.  
OPERATION : UPRIGHT  
SPECIFICATION : IS : 6204  
JET LENGTH : 06 TO 10 MTRS.  
DISCHARGE TIME : 60 TO 120SEC.  
% OF DISCHARGE : 95 TO 98%

TRADE MARK  
**Fire Fite**®



BHARATI FIRE ENGINEERS, THE MANUFACTURERS OF **Fire Fite** BRAND FIRE EXTINGUISHERS COMBINE THE STRENGTH OF TWO DECADE OF EXPERTISE WITH HIGHLY ACCLAIMED TECHNICAL MANPOWER THAT'S AND QUALITY CONSCIOUS AT EVERY STAGE. THE MANUFACTURING SYSTEM INNOVATIVE IS CERTIFIED TO **BS EN ISO 9001 : 2000 / ISO 9001** . ALL **Fire Fite** BRAND FIRE EXTINGUISHERS ARE MANUFACTURED CONFORMING TO **BIS STANDARDS AND ISI MARK** PACKED WITH THE EXCLUSIVE SALES AND SERVICE NETWORK THROUGHOUT THE COUNTRY.



**BHARATI FIRE ENGINEERS**

3/6, ANUPAM INDUSTRIAL ESTATE, NEAR SAI DHAM BLDG.,  
L.B.S. MARG, MULUND (W), MUMBAI - 400 080.  
TEL: 5601169 TELEFAX: 568 1269 / 568 5159 GRAM "SMARTFIRE"